

DENSEI-LAMBDA

SPECIFICATIONS

MYB-12 -33

G023-01-01

Items		Model	MYB-1250	MYB-1270	MYB-1290	
			-33	-33	-33	
1	Rated Voltage (AC,DC)	V	250			
2	Rated Current (AC,DC) * Note 1	A	50	70	90	
3	Test Voltage (terminals to case, 1min AC)	V	2500 (at 25°C, 70% RH)			
4	Insulation Resistance (terminals to case, 500V DC)	MΩ	300 min (at 25°C, 70% RH)			
5	Leakage Current	125V 60Hz	0.5 max			
		250V 60Hz	1 max			
6	DC Resistance	mΩ	2.5 max	1.9 max	1.3 max	
7	Temperature Rise	°C	35 max			
8	Operating Temperature	°C	-25 ~ +85			
9	Operating Humidity	%	30% ~ 90% RH (No Dewdrop)			
10	Storage Temperature	°C	-30 ~ +85			
11	Storage Humidity	%	10% ~ 95% RH (No Dewdrop)			
12	Vibration	-	10~55~10 Hz , Amplitude (Sweep for 1 min) 1.5 mm X.Y.Z 2 hour each			
13	Safety standards	-	Duilt to meet UL , CSA			
14	Weight	g	2000 typ	2900 typ	3000 typ	

*Note 1 : Value for $T_a \leq 50^\circ\text{C}$
For $T_a > 50^\circ\text{C}$, derate
according to the derating
curve shown on the right.

