

CONNECTORS USED :

PART DESCRIPTION	PART NAME	MANUFACTURER	QTY
PIN HEADER (INPUT SIDE CN1)	B3(7.5)B-XH-A	J.S.T	1
PIN HEADER (OUTPUT SIDE CN2)	B4B-XH-A	J.S.T	1


MATCHING HOUSINGS & PINS :

* NOT INCLUDED WITH THE PRODUCT.

PART DESCRIPTION	PART NAME	MANUFACTURER	QTY
SOCKET HOUSING (CN1)	XHP-7	J.S.T	1
SOCKET HOUSING (CN2)	XHP-4	J.S.T	1
TERMINAL PINS (CN1,2)	BXH-001T-P0.6 OR SXH-001T-P0.6	J.S.T	7

HAND CRIMPING TOOL : YC-110R CN1,2 MANUFACTURER : J.S.T
: YRS-110 CN1,2 MANUFACTURER : J.S.T

NAME PLATE



SEE NOTE B

SEE NOTE C

NOTES :

- A : THE 4XØ3.5 HOLES ARE CUSTOMER CHASSIS MOUNTING HOLES. ALL MUST BE SCREWED IN ORDER TO CONFORM THE VIBRATION SPEC.
- B : MODEL NAME, NOMINAL OUTPUT VOLTAGE, MAXIMUM OUTPUT CURRENT ARE SHOWN HERE IN ACCORDANCE WITH THE SPECIFICATIONS.
- C : COUNTRY OF MANUFACTURE WILL BE SHOWN HERE.
- D : TO KEEP THE DISTANCE MORE THAN 2mm BETWEEN PC-BOARD EDGE AND CUSTOMER CHASSIS.

(unit : mm)

MODEL NAME	VS15C
DENSEI-LAMBDA	

CA710-02-01B