



NOTES

- A: M4 EMBOSSED TAPPED & COUNTERSUNK HOLES (6) ARE FOR CUSTOMER CHASSIS MOUNTING. SCREW MUST NOT PROTRUDE INTO POWER SUPPLY BY MORE THAN 6mm.
- B: $\phi 4.5$ HOLES (4) AND R2.25 SLOT HOLES (3) ARE FOR CUSTOMER CHASSIS MOUNTING. (USE M4 MOUNTING SCREW.)
- C: MODEL NAME, NOMINAL INPUT VOLTAGE, NOMINAL OUTPUT VOLTAGE, MAXIMUM OUTPUT CURRENT, PEAK OUTPUT CURRENT AND COUNTRY OF MANUFACTURE ARE SHOWN HERE IN ACCORDANCE WITH THE SPECIFICATIONS.

D: FG IS FOR SAFETY GROUND CONNECTION.

E: REMOTE ON/OFF CONTROL CONNECTOR (CN2,CN52) : B2B-XH-AM (J.S.T.)
 *CN2 IS NORMALLY SHORTED BY JM-2W-96(J.S.T.)
 MATCHING HOUSING : XHP-2 (J.S.T.)
 MATCHING TERMINAL : BXH-001T-P0.6 (J.S.T.) OR SXH-001T-P0.6 (J.S.T.)
 HAND CRIMPING TOOL : YC-110R OR YRS-110 MANUFACTURER : J.S.T.

(unit : mm)

MODEL NAME	ZWS150PAF/TL
DENSEI-LAMBDA	

CA723-02-01/TL-A