



NOTES:

- A.THE 5- ϕ 3.5 HOLES ARE CUSTOMER'S CHASSIS MOUNTING HOLES. ALL MUST BE SCREWED IN ORDER TO CONFORM THE VIBRATION SPEC.
- B.MODEL NAME, INPUT VOLTAGE RANGE, NOMINAL OUTPUT VOLTAGE, MAXIMUM OUTPUT CURRENT ARE SHOWN HERE IN ACCORDANCE WITH THE SPECIFICATIONS.
- C.COUNTRY OF MANUFACTURE WILL BE SHOWN HERE.
- D.TO KEEP THE DISTANCE MORE THAN 4m/m BETWEEN PC-BOARD EDGE AND CUSTOMER'S CHASSIS.
- E.FG IS FOR SAFETY GROUND CONNECTION.
- F.REMOTE ON/OFF CONTROL CONNECTOR (CN2,CN52) : B2B-XH-AM (J.S.T.)
*CN2 IS NORMALLY SHORTED BY JM-2W-96(J.S.T.)
MATCHING HOUSING : XHP-2 (J.S.T.)
MATCHING TERMINAL : BXH-001T-P0.6 (J.S.T.) OR SXH-001T-P0.6 (J.S.T.)
HAND CRIMPING TOOL : YC-110R OR YRS-110 MANUFACTURER : J.S.T.

(unit : mm)

MODEL NAME	ZWS240PAF/T
DENSEI-LAMBDA	

CA724-02-01/T